

HYPRO 600 - 635W TH3G66M


Bifacial Dual Glass
0BB Half Cell N-type HJT

KEY FEATURES


- Better Shading Tolerance
- Ultra-High Bifacial Factor
- Ultra-High Power Generation
- Most Stable Power Temperature Coefficient
- Lead Technology of Metallization Process
- Excellent Anti-LID & Anti-PID Performance

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems



PERFORMANCE WARRANTY



15 Years
Product Warranty

30 Years
Linear Power Warranty

1%
First-year Degradation

0.30 %
Annual Degradation 30 Years


TALESUN-TH3G66M

132-Half-Cell Bifacial HJT Module


• BloombergNEF Tier 1 PV module manufacturer

Engineering Drawings

Unit: mm



I-V Curve (620W)



Temperature Coefficients

Temperature Coefficient of Pmax	-0.24%/ °C
Temperature Coefficient of Voc	-0.22%/ °C
Temperature Coefficient of Isc	+0.04%/ °C

Operating Conditions

Nominal Operating Cell Temp.	44±2°C
Operating Temperature	-40~+85°C
Maximum System Voltage	DC1500V
Maximum Series Fuse Rating	30A
Tolerance of Pmax	0~+3%
Power Selection	0~+5W
Bifaciality	90±5%
Safety Class	Class II

Mechanical Characteristics

Cell Type	HJT
No. of Cells	132 (6x22)
Dimensions	2382x1134x30mm
Weight	32.6kg
Junction Box	IP68
Cable	4mm²; +350/-250mm or customized; UV resistant
Connector	MC4 / MC4-Evo2 / MC4-Evo2A / PV-H4 / Z4S-abcd / PV-ZH202B
Frame	Anodized aluminum alloy frame
Max Static Load (front side/rear side)	5400Pa / 2400Pa
Glass	Dual glass, 2.0mm

Electrical Characteristics

STC

TALESUN-TH3G66M	600	605	610	615	620	625	630	635
Maximum Power (Pmax/W)	600	605	610	615	620	625	630	635
Module Efficiency (%)	22.2	22.4	22.6	22.8	23.0	23.1	23.3	23.5
Voltage at Pmax (Vmp/V)	40.69	40.78	40.85	40.96	41.05	41.14	41.23	41.32
Current at Pmax (Imp/A)	14.76	14.85	14.95	15.03	15.12	15.21	15.30	15.39
Open Circuit Voltage (Voc/V)	48.75	48.85	48.94	49.05	49.15	49.25	49.34	49.43
Short Circuit Current (Isc/A)	15.56	15.66	15.76	15.86	15.96	16.06	16.16	16.26

STC: AM1.5, 1000W/m², 25°C.

BNPI

Maximum Power (Pmax/W)	672	678	684	689	695	700	706	712
Voltage at Pmax (Vmp/V)	40.83	40.92	40.99	41.10	41.19	41.28	41.37	41.46
Current at Pmax (Imp/A)	16.48	16.58	16.69	16.78	16.88	16.98	17.08	17.18
Open Circuit Voltage (Voc/V)	48.92	49.02	49.11	49.22	49.32	49.42	49.51	49.60
Short Circuit Current (Isc/A)	17.45	17.56	17.67	17.79	17.90	18.01	18.12	18.24

BNPI: AM1.5, 1000W/m², 135W/m², 25°C.

NOCT

Maximum Power (Pmax/W)	458	461	465	469	473	477	481	484
Voltage at Pmax (Vmp/V)	38.84	38.92	38.98	39.09	39.18	39.26	39.34	39.42
Current at Pmax (Imp/A)	11.80	11.87	11.95	12.01	12.08	12.16	12.23	12.30
Open Circuit Voltage (Voc/V)	46.53	46.62	46.71	46.82	46.91	47.01	47.09	47.18
Short Circuit Current (Isc/A)	12.44	12.52	12.60	12.68	12.76	12.84	12.92	13.00

NOCT: AM1.5, 800W/m², 20°C, 1m/s.

Packaging

	40HQ
Modules Per Pallet	36
Pallets Per Container	20
Modules Per Container	720



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Suzhou Talesun Solar Technologies Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.